



| 公差等级/General Tolerances(mm) | | 公差等级/General Tolerances(mm) | | | | | | | | | | 公差等级/General Tolerances(mm) | | |
|---|----|-----------------------------|-----|-----|-----|-----|-----|------|------|------|------|-----------------------------|------|--------|
| 0 | >3 | >6 | >10 | >18 | >30 | >50 | >80 | >120 | >180 | >250 | >315 | >400 | >500 | 0.1/10 |
| 3 | 6 | 10 | 18 | 30 | 50 | 80 | 120 | 180 | 250 | 315 | 400 | 500 | >500 | ±Z |
| ±0.12 ±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50 | | | | | | | | | | | | | | |

| | | | |
|---|-----------------|-------|-----------|
| 3 | Current carrier | Steel | Zn Plated |
| 2 | Screws | Steel | Zn Plated |
| 1 | Housing | PA66 | UL94V-2 |

| | | | |
|--|---------------|--------|--------|
| UL 标准 /UL Standard: | B | C | D |
| 额定电压/电涌 /Rated Voltage(V)/Current(A) | 300/20 | / | 300/70 |
| IEC 标准 /IEC Standard: | III/3 | III/2 | II/2 |
| 过压类别 /Overvoltage Category/污秽等级 /Pollution Degree | / | / | / |
| 额定电压/电涌 /Rated Voltage(V)/Current(A) | / | 750/57 | / |
| 额定冲击电压 (kV) /Rate Impulse Voltage(kV) | / | 3.0 | / |
| 拧紧扭矩 /Torque Tightening(N·m/Lb·in) | M4: 1.2/10.53 | | |
| 导线范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG) | 1.0~10/12 | | |
| 间距 /Pitch(mm) /线数范围 /Poles | 15.0 | | |
| 剥线长度 /Stripping length(mm) | 10 | | |
| 使用温度范围 /Operating temperature(°C) | -40~+105 | | |
| 符合 RoHS 环保要求 /Conform to RoHS | Yes | | |

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
DG15HSWP-1.2-XXP-1Y-100A(H)

DRAWING NO.: DG15HSWP-1.2-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET 1/1

| REV | ECN | DESCRIPTION | DRAFT | DATE | SIZE: A4 | SCALE: 1:1 | SHEET 1/1 |
|-----|-----|-------------|-------|------|----------|------------|-----------|
| | | | | | | | |

D
C
B
A

1 2 3 4 5 6