



未注公差/General tolerances(mm)												
0	>3	>6	>1	>1	>3	>5	>8	>1	>2	>31	>4	0.2/1.0
~	~	~	~	~	~	~	~	~	~	~	~	
3	6	10	18	30	50	80	120	180	25	5	0	±2
±0.12	±0.20	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	

推荐面板安装尺寸  
推荐面板厚度 ≥ 5mm

### 型号说明

SA-EBC-2105-F-00A(H)

插座  
组装式  
系列名称  
母端  
通用型环保产品

产品插针数量  
功率针 2pin,  
PE针 1pin,  
信号针 5pin

REV	ECN	DESCRIPTION	DRGT	20MMX2X
(10)			XX	X

MATERIAL:	/	NAME:	SA-EBC-2105-F-00A(H)
MAT NO.:	/	DRFT:	Huangju 2021.8.23
STATUS:	/	TYPE:	CUSTOMER DRAWING
APPD:	/	SCALE:	2:1
CHKD:	/	REV	T0

额定电压/Rated Voltage	110V/50A
额定电流/Rated Current	110V/50A
绝缘电阻/Insulation resistance	≥100MΩ
插拔次数/Mechanical working life(cycles)	3000
耐电压/Withstanding voltage	500V AC
使用温度范围/Operating temperature(°C)	-40~+85
防水等级/Levels of protection	IP67(Single)
接线方式/Terminal	Soldering
SURFACE:	/

**DEGSON** 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD