



尺寸 (mm)		General Dimension (mm)	
0	2.54	1.018	1.270
3	6.35	2.518	3.175
6	10.16	4.015	4.900
10	16.51	6.665	8.125
15	23.81	9.965	12.250
20	31.11	13.265	16.375
25	38.41	16.565	20.500
30	45.71	19.865	24.625
35	53.01	23.165	28.750
40	60.31	26.465	32.875
45	67.61	29.765	37.000
50	74.91	33.065	41.125
55	82.21	36.365	45.250
60	89.51	39.665	49.375
65	96.81	42.965	53.500
70	104.11	46.265	57.625
75	111.41	49.565	61.750
80	118.71	52.865	65.875
85	126.01	56.165	70.000
90	133.31	59.465	74.125
95	140.61	62.765	78.250
100	147.91	66.065	82.375

6	Nut	Copper alloy	/
5	Pin	Copper	Sn Plated
4	Cage	Copper alloy	Ni Plated
3	Screw	Steel	M3/In filled
2	COVER	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压 / Rated Voltage (V)	300/15	/	300/10
额定电流 / Rated Current (A)	3	2	1.5
IEC 标准 / IEC Standard:	III/3	III/2	II/2
过压类别 / Overvoltage Category / 污秽等级 / Pollution Degree	/	400/20	/
额定电压 / Rated Voltage (V)	/	400	20
额定电流 / Rated Current (A)	/	4	/
额定脉冲电压 / Rated Impulse Voltage (KV)	/	M3.6	/
额定拧紧力矩 / Rated Tightening Torque (kgf·cm)	/	0.2~2.5	28~12
弹性模量 / Modulus of Elasticity (GPa)	/	7.62	N=02~16P
可焊 / Solderable	/	7~8	/
剥线长度 / Stripping Length (mm)	/	-40~+105	/
使用温度范围 / Operating Temperature (°C)	/	Yes	/
符合 RoHS 环保要求 / Conform to RoHS	/		

MATERIAL: SURFACE: /

NINGBO DESON ELECTRICAL CO., LTD
 ZEDGKRP-7.62-XXP-1Y-00A(H)
 DRAWING NO.: 10002065
 TYPE: CUSTOMER DRAWING
 SCALE: 2.5:1 SHEET 1/1

REV	ECON	DESCRIPTION	DRT	DATE
1				