

Panoramica

Informazioni sul prodotto



Interface module-DM50-MDR-20-20-4Y-00A(H)-30040000065

MDR module,input/output module,with screw connectorand MDR connector,can be installed on DIN35 rail,20 positions

Vantaggi del prodotto

20digits to 50digits

1:1 connection

Screw connection

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	0.5A
Signal points	20
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	MDR connection
Connection volume	1
Number of digits	20
spacing	1.27mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	22
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	81mm
width	57mm

Height	42mm
--------	------

Accessori

Accessories

Wire harness	DX220-3S-500-00A(H)
--------------	---------------------

Dati aziendali

numero d'ordine	30040000065
Unità di imballaggio	1
Quantità di ordine minimo	10
Peso dei prodotti (senza imballaggio)	115