

Panoramica

Informazioni sul prodotto

**Interface module-DM50-IDC-10-10-4Y-00A(H)-30040000056**

IDC module,input/output module,with screw connector and IDC stitching line,can be installed on DIN35 rail,10 positions

Vantaggi del prodotto

10digits to 50digits

1:1 connection

Screw connection

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	10
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	66mm
width	57mm

Height	44mm
--------	------

Accessori

Accessories

Wire harness	DX211-1S-500-00A(H)
--------------	---------------------

Dati aziendali

numero d'ordine	30040000056
Unità di imballaggio	6
Quantità di ordine minimo	12
Peso dei prodotti (senza imballaggio)	55