

Panoramica

Informazioni sul prodotto



Interface module DM50-IDC-10-10-4G-00A(H)-30040000055

IDC module, japanese terminal block, with screw connector and IDC stitching line, can be installed on DIN35 rail, 10 positions

Vantaggi del prodotto

10digits to 50digits

1:1 connection

Screw connection

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-20 °C ... 70 °C
---	------------------

Standards/Regulations

Standards/Regulations	IEC61810
-----------------------	----------

Pollution level	3
-----------------	---

Overvoltage category	III
----------------------	-----

Rated overvoltage	0.5kV
-------------------	-------

Flame retardant grade, in line with UL94	V0
--	----

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	10
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	0.3mm ² --2.0mm ²
Connectable guide cross section AWG	22-14AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3
Hard wire cross section	0.3mm ² --2.0mm ²

Dimension

length	66mm
width	57mm

Height	44mm
--------	------

Accessori

Accessories

Wire harness	DX211-1S-500-00A(H)
--------------	---------------------

Dati aziendali

numero d'ordine	30040000055
Unità di imballaggio	6
Quantità di ordine minimo	12
Peso dei prodotti (senza imballaggio)	70