

Panoramica

Informazioni sul prodotto

**5A-GF-0.52-92116900030**5A silver gold female pins, Adapter wire specification 0.52mm²

Vantaggi del prodotto

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

☐

Marking

classification	Contact
Series	5A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	0.52mm²
Conductor cross sections(AWG)	20AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	8mm
working life-mating cycles	≥500

Accessori

Dati aziendali

numero d'ordine	92116900030
Unità di imballaggio	100
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	0.241