

## Panoramica

## Informazioni sul prodotto

**D32A-BK-4g-CV-21010000375**

32A Lower base, Four levers, no back cover, Wear protective cover

## Vantaggi del prodotto

- ✓ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ✓ Various installation methods and outlet directions to meet on-site wiring requirements;
- ✓ Snap-in combination structure, dustproof, waterproof, easy operation;

## Certificazione del prodotto

## Dati tecnici

## Disegno del prodotto

## Modello 3D

□

## Marking

|                |                         |
|----------------|-------------------------|
| classification | Upper Housing/base      |
| Series         | A                       |
| Type           | Hole mounting base      |
| Description    | With plastic dust cover |
| Specification  | Low structure           |

## versions

|                  |             |
|------------------|-------------|
| Dimension        | 32A         |
| locking Category | Double lock |

## Material characteristics

|                               |                          |
|-------------------------------|--------------------------|
| Flammability rating           | V-0                      |
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |
| Material (seal)               | NBR                      |

Technical specification

|                       |               |
|-----------------------|---------------|
| Limiting temperatures | -40°C~~+125°C |
| IP class              | IP65          |

Accessori

Dati aziendali

|                                       |             |
|---------------------------------------|-------------|
| numero d'ordine                       | 21010000375 |
| Unità di imballaggio                  | 100         |
| Quantità di ordine minimo             | 1           |
| Peso dei prodotti (senza imballaggio) | 148         |