

Panoramica

Informazioni sul prodotto



D10A-SF-1L-CV-2PG16-21010000168

10A Lower base,single buckle,back cover ,side entry,double PG16 Thread hole,Wear protective cover

Vantaggi del prodotto

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Upper Housing/base
Series	A
Type	Surface mount base
Description	With plastic dust cover
Specification	Low structure

versions

Dimension	10A
locking Category	Single lock
Thread specification	2x PG16

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40℃~+125℃
IP class	IP65

Accessori

Dati aziendali

numero d'ordine	21010000168
Unità di imballaggio	100
Quantità di ordine minimo	1
Peso dei prodotti (senza imballaggio)	182.6