

Panoramica

Informazioni sul prodotto

**D10A-SF-1L-PG16-21019000178**

10A Lower base, single buckle, back cover, side entry, PG16 Thread hole

Vantaggi del prodotto

- ✓ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ✓ Various installation methods and outlet directions to meet on-site wiring requirements;
- ✓ Snap-in combination structure, dustproof, waterproof, easy operation;

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Upper Housing/base
Series	A
Type	Surface mount base
Specification	Low structure

versions

Dimension	10A
locking Category	Single lock
Thread specification	1x PG16

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40°C~+125°C
IP class	IP65

Accessori

Dati aziendali

numero d'ordine	21019000178
Unità di imballaggio	100
Quantità di ordine minimo	1
Peso dei prodotti (senza imballaggio)	162.5