

Panoramica

Informazioni sul prodotto



DA-003-F-21020000001

Heavy-duty insert, Number of contacts: 3+PE, Dimension: 3A, Rated voltage : 400/230V, Rated current: 10A, Female insert, Screw connector

Vantaggi del prodotto

- ☒ Screw connection technology, applicable to a wide range of wire specifications;
- ☒ No need special tools, easy to operate;
- ☒ Less materials, easy to manage;
- ☒ With grounding protection.

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Insert
Series	DA

versions

Connection method	Screw connection
Female/Male	Female
Dimension	3A
Number of positions	3
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	4.5mm
Rated torque	0.25N.m
Conductor cross sections (mm²)	0.75-1.5mm²
Conductor cross sections(AWG)	18-16AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessori

Accessories

Screwdriver

/

Dati aziendali

numero d'ordine	21020000001
Unità di imballaggio	100
Quantità di ordine minimo	5
Peso dei prodotti (senza imballaggio)	12.78