

Panoramica

Informazioni sul prodotto

**FY-M12D-04M-M12D-04F-T-0100-20030002023**

M12D-Y distributor(PCB),Input terminal:Male,Output terminal:4 cord Female

Vantaggi del prodotto

- ✓Single wire input, Multi wire output
- ✓Cost saving and convenient installation
- ✓Protection level:IP67/68
- ✓Widely used in industrial automation, rail transit and other industries

Certificazione del prodotto

RoHS REACH

Dati tecnici

Disegno del prodotto

Modello 3D

□

Environmental conditions

Ambient temperature

-25°C...85°C

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100

Material

Flammability rating ,in line with UL97	HB
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Accessori

Dati aziendali

numero d'ordine	20030002023
Unità di imballaggio	/
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	/