

## Panoramica

## Informazioni sul prodotto

**PM-M12A-05P-FF-SR8B01-20030000680**

Sensor/Actuator Cable,PUR,black,UL20549,Female plug,acodado M12,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m

## Vantaggi del prodotto

- ✓ Sealing optimization, protection level up to IP68
- ✓ Meet the harsh environment
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

## Certificazione del prodotto

**RoHS REACH**

## Dati tecnici

## Disegno del prodotto

## Modello 3D

□

## Environmental conditions

Ambient temperature

-25°C...80°C

IP class

IP68

## General parameters

Rated current

4A

60V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

|                             |        |
|-----------------------------|--------|
| Overvoltage level           | II     |
| Pollution level             | 3      |
| Insertion and pullout cycle | ≥ 100  |
| Torque                      | 0.4 Nm |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL94 | V0                        |
| Flammability rating ,in line with UL97 | HB                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PU                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

Standards and specifications

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |
|--------------------------|-----------------|

Cable

|                                            |                                       |
|--------------------------------------------|---------------------------------------|
| Cable type                                 | PUR Black                             |
| Cable type(abbreviation)                   | PUR                                   |
| UL AWM form                                | UL20549                               |
| Cross section                              | 0.34mm <sup>2</sup>                   |
| AWG signal wire                            | 22AWG                                 |
| Wire structure Signal wire                 | 17/0.16mm <sup>2</sup>                |
| Core diameter (including insulation layer) | 1.30±0.05mm                           |
| Wire color                                 | 1 Brown 2 White 3 Blue 4 Black 5 Gray |
| Thickness, insulation                      | 0.6mm                                 |

|                               |                                      |
|-------------------------------|--------------------------------------|
| Cable outer diameter D        | 5.4 ±0.2mm                           |
| Outer sheath, material        | PU                                   |
| Conductor insulation material | PE                                   |
| Conductor material            | Tinned copper                        |
| Insulation resistance         | ≥100MΩ                               |
| Conductor resistance          | Maximum 59.4Ω/km (at 20 °C )         |
| Nominal cable voltage         | 300V                                 |
| Cable test voltage            | 2000V                                |
| Flame retardant               | Comply with UL 758/1581 FT2 standard |
| Oil resistance                | No                                   |
| Dimension                     |                                      |
| Cable length                  | 1m                                   |

Accessori

Accessories

|             |                 |
|-------------|-----------------|
| Sealing cap | CAP-M12-MP-8001 |
|-------------|-----------------|

Dati aziendali

|                                       |             |
|---------------------------------------|-------------|
| numero d'ordine                       | 20030000680 |
| Unità di imballaggio                  | /           |
| Quantità di ordine minimo             | 100         |
| Peso dei prodotti (senza imballaggio) | /           |