

Panoramica

Informazioni sul prodotto



DG46S-B-60(H)-12030000233

Single-layer PCB barrier terminal blocks, Rated current:30A. Rated voltage (UL) :300V, Cross section:22-10AWG, pitch:9.5mm, Color:black, Contact surface :Tin

Vantaggi del prodotto

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Solder plate mounting for electrical connection of the device to the PCB

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

AWG	22~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	25A

Item properties

Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver

screw thread	M4
Pitch	9.5mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessori

Accessories

Bridge	K24
--------	-----

Dati aziendali

numero d'ordine	12030000233
Unità di imballaggio	100
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	5.83

