


Panoramica

Informazioni sul prodotto



DGR10-10A(H)-12010000069

Transfer barrier terminal blocks, Rated current: 10A. Rated voltage (UL) : 600V, Cross section: 24~16AWG, pitch: 7.3mm, Color: black, Contact surface: Tin

Vantaggi del prodotto

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

AWG	24~16AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	10A
Rated current (D)	5A

Rated current (C)	10A
-------------------	-----

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	7.3mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Accessori

Accessories

--	--

Dati aziendali	
numero d'ordine	12010000069
Unità di imballaggio	16
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	39