

Panoramica

Informazioni sul prodotto

**TS2.5-10070000007**

Transformer terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 800V, Color: Orange, Contact surface : Tin

Vantaggi del prodotto

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

Conductor cross section solid	0.5~2.5mm ²
Conductor cross section flexible	0.5~2.5mm ²
AWG	24~14AWG
Torque	0.5N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated current (B)	10A

Rated current (C)	10A
-------------------	-----

Electrical parameters IEC

Rated current	800V
	24A
Rated current(III/2)	800V

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	7.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessori	
Accessories	
Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Dati aziendali	
numero d'ordine	10070000007
Unità di imballaggio	600
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	5.83