

Panoramica

Informazioni sul prodotto

**TS10-10070000003**

Transformer terminal blocks, Rated current: 57A. Rated voltage
(III/2) : 750V, Color: Orange, Contact surface : Tin

Vantaggi del prodotto

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

Conductor cross section solid	4.0~10mm ²
Conductor cross section flexible	4.0~10mm ²
AWG	12~6AWG
Torque	2N.m
Strip length	16mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated current (B)	55A

Rated current (C)	55A
-------------------	-----

Electrical parameters IEC

Rated current	750V
	57A
Rated current(III/2)	750V
Rated surge voltage(III/2)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M5
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessori

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10070000003
Unità di imballaggio	165
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	24.24