

Panoramica

Informazioni sul prodotto



DG136HT-12.7-10040001968

PCB terminal blocks, Rated current: 65A, Rated voltage (III/2) 1000V, Cross section: 2.5-16mm², pitch: 12.7mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

Vantaggi del prodotto

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Different poles can be combined through the side lock

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

2.5~16mm²

Conductor cross section flexible

2.5~16mm²

AWG

20~6AWG

Torque

1.2N.m

Strip length

10mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	60A
Rated current (D)	5A
Rated current (C)	60A

Electrical parameters IEC

Rated voltage	1000V
Rated current	65A
Rated current(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	12.7mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper

Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessori

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

Dati aziendali

numero d'ordine	10040001968
Unità di imballaggio	170
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	16.74

