

Panoramica

Informazioni sul prodotto



Bus IO-DF750-HT-001-11-1001A(H)-30050000253

Card IO housing,push-instructure,Can be matched bring light RJ45Connector,LEDinstruct

Vantaggi del prodotto

- ☒ Dual network port without light RJ45 interface
- ☒ 8-bit address interface
- ☒ Internal bus through bottom 6 gold-plated terminals
- ☒ Equipped 16aislePower Module ,LEDs per node
- ☒ Internal 2 gold-plated blade connectors for power cascading expansion
- ☒ Can be installed on DIN rail

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40°C ~ +70°C
Ambient temperature (storage / transport)	-40°C ~ +70°C

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	48mm
Height	69mm

Accessori

Dati aziendali

numero d'ordine	30050000253
Unità di imballaggio	20 SKT
Quantità di ordine minimo	20 SKT
Peso dei prodotti (senza imballaggio)	122.5g