

Panoramica

Informazioni sul prodotto



Relay base-DPSF06A-E3-00A(H)-30020000065

DPSFrelay base,used for1PDTrelay,screw connection

Vantaggi del prodotto

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 6A, 1PDTgrade
- ☒ Arc partition between adjacent columns
- ☒ Anti-touch cover at the top of the screw

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Environmental data

Ambient temperature (operation)

-40°C ~ +70°C

Ambient temperature (storage / transport)

-40°C ~ +70°C

Technical data

Rated voltage UN

300V

Installation location

Arbitrary

Assembly instructions

DIN35 rail

Connection data 1

Connection name

enter

Connection method

Screw connection

Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	96.5mm
width	6.2mm
Depth including bracket	81mm

Accessori

Dati aziendali

numero d'ordine	30020000065
Unità di imballaggio	20 SKT
Quantità di ordine minimo	20 SKT
Peso dei prodotti (senza imballaggio)	56g