

Panoramica

Informazioni sul prodotto



Relay base-DSRC05A-F3-00A(H)-30020000063

DSRCrelay base,used for1PDTrelay,screw connection

Vantaggi del prodotto

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A, 1 PDT grade
- ☒ Arc partition between adjacent columns
- ☒ Strong and weak electricity separation

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

☐

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65°C

Technical data

Rated voltage UN	300V
Rated current IN	10A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
-----------------	-------

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	80mm
width	16mm
Depth including bracket	61.5mm

Accessori

Dati aziendali

numero d'ordine	30020000063
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	