

Panoramica

Informazioni sul prodotto



DG66H-B-12030000151

Single layer PCB fence terminal,nominal current30A.Rated voltage(UL): 600V,Rated cross section:22~10AWG,pitch:11.5mm,Color:black,Contact surface:Tin

Vantaggi del prodotto

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Solder board installation, which can realize the electrical connection between the device and the PCB

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

AWG	22~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	30A
	55A
Rated current (D)	5A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M4
Pitch	11.5mm
Number of potentials	9
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-30°C~120°C
---------------------------------	-------------

Accessori

Accessories

--	--

Dati aziendali

numero d'ordine	12030000151
Unità di imballaggio	10
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	60.26