

Panoramica

Informazioni sul prodotto



DG2020-B-12010000505

Single layer PCB fence terminal,nominal current115A.Rated voltage(UL): 600V,Rated cross section:18~3AWG,pitch:20.2mm,Color:black,Contact surface:Tin

Vantaggi del prodotto

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Can meet the Max current electrical connection of the power end

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

AWG	18~3AWG
Torque	7.9N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	115A
Rated current (D)	5A
Rated current (C)	115A

Item properties

Type of installation	PCB welding
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M6
Pitch	20.2mm
Number of potentials	11
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~120°C
---------------------------------	-------------

Accessori

Accessories

--	--

Dati aziendali

numero d'ordine	12010000505
Unità di imballaggio	12
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	387.5