

Panoramica

Informazioni sul prodotto



RM-EBBH-2006-M-1000-00A(H)-250800000001

Charging and discharging plug at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω; Protection grade: IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 20N; Working temperature: - 40 ~ 105 °C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Vantaggi del prodotto

- ☒ Compact structure and high space utilization
- ☒ Adopt bayonet locking structure to prevent accidental unlocking
- ☒ Direct plug operation, convenient and fast
- ☒ Signal pin No.: 0~8 pins
- ☒ Multiple auditory and visual feedback are inserted in place
- ☒ Beautiful appearance, fit human functional design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

Series	DA
	DD
	DF

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	15
	25
	32
	42

Accessori

Dati aziendali	
numero d'ordine	25080000001
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	