

Panoramica

Informazioni sul prodotto



K48-700A(H)-10900000168

Metal Part,nominal current:30A,screw thread Specification:M4,Contact surface:Tin

Vantaggi del prodotto

- ☑ Technology of riveting nut in post process, excellent torque
- ☑Suitable for in-unit installation

Certificazione del prodotto

| D | | |
|--------|------|--|
| I lati | tecn | |
| Dau | LECH | |

Disegno del prodotto

Modello 3D

Processing notes

| Process | Wave soldering/manual soldering |
|---------|---------------------------------|
|---------|---------------------------------|

Connection capacity

| Torque | 1.2N.m |
|--------|--------|
| | |

Item properties

| Type of installation | PCB welding |
|----------------------|------------------|
| Connection method | Screw connection |
| screw thread | M4 |
| Number of potentials | 1 |
| Pluggable or not | no |

Material data

| Environmental items | Compliant with REACH/RoHS |
|----------------------------|---------------------------|
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |

| Accessori | | | |
|-----------|--|--|--|
| | | | |

| ati aziendali | |
|---------------------------------------|------------|
| numero d'ordine | 1090000168 |
| Unità di imballaggio | 250 |
| Quantità di ordine minimo | |
| Peso dei prodotti (senza imballaggio) | 3.39 |