

Panoramica

Informazioni sul prodotto

**DGBSC-SG02/4-10080000436**

Building wiring terminals, Rated current: 32A. Rated voltage (III/2): 450V, max. 4 mm², Color: transparent, Contact surface: Tin

Vantaggi del prodotto

- ☒ Rotatable operating handle, easy to operate
- ☒ Suitable for all conductors types
- ☒ Suitable for field wiring, saving installation time

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

☐

Connection capacity

Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (C)	600V
-------------------	------

Electrical parameters IEC

Rated voltage	450V
Rated current	32A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Shell color	Transparent
Flammability rating	UL94V-2

Environmental data

Ambient temperature (operation)	-40°C~85°C
---------------------------------	------------

Accessori

Dati aziendali

numero d'ordine	10080000436
Unità di imballaggio	100
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	3.22

