

Panoramica

Informazioni sul prodotto



9EDGKD-HC-7.5-10020007568

Pluggable terminal blocks, Rated current: 25A. Rated voltage
(III/3) : 630V, pitch: 7.5mm, Color: black, Contact surface : Tin

Vantaggi del prodotto

- ☒ Push-in spring connection, easy wiring
- ☒ SNAP-LOCK series, with self-locking buckle

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Packaging information

Type of packaging

box-packed

Connection capacity

Conductor cross section solid

1.0~6mm²

Conductor cross section flexible

1.0~6.0mm²

AWG

18~10AWG

Strip length

12mm

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated current (B)	25A
Rated current (C)	25A

Electrical parameters IEC

Rated voltage	800V
Rated current(III/3)	630V
Rated current	25A
Rated current(III/2)	800V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection method	Push-in spring connection
Pitch	7.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessori	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

Dati aziendali	
numero d'ordine	10020007568
Unità di imballaggio	240
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	13.2