

Panoramica

Informazioni sul prodotto

**DG200D-A-02P-13-00Z(H)-12050000299**

Transfer Type, Rated current: 200A. Rated voltage: : 600V, Cross section: 2~3/0AWG , Pitch: 27mm, Color: black, Contact surface: Ni

Vantaggi del prodotto

- ☒ Screw connection for worldwide use
- ☒ Barrier wiring structure, stable and reliable connection
- ☒ High current electrical connections at power end can be met

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

AWG	2~3/0AWG
Torque	6.0N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	200A
Rated current (D)	5A

Rated current (C)	200A
-------------------	------

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	2
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Nickel plating
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Overview

Connection method	screw connection
-------------------	------------------

Accessori

Dati aziendali	
numero d'ordine	12050000299
Unità di imballaggio	12
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	180